CASIO


Getting Acquainted

MO0602-EA

Congratulations upon your selection of this CASIO watch. To get the most out of your purchase, be sure to read this manual carefully.

Keep the watch exposed to bright light The electricity generated by the solar cell of the watch is stored by a built-in battery. Leaving or using the watch

Bright Light Solar cell Solar cell






You should try to keep the watch outside of your sleeve
You should try to keep the watch outside of your sleeve

where it is not exposed to light causes the battery to run down. Make sure the watch is exposed to light as much as


as much as possible. Charging is reduced significantly if the face is only partially covered.

The watch continues to operate, even when it is not exposed to light. Leaving the watch in the dark can cause the battery to run down, which will result in some watch functions to be disabled. If the battery goes dead, you will have to re-configure watch settings after recharging. To ensure normal watch operation, be sure to keep it exposed to light as much as possible.



General Guide

Press (B) to change from mode to mode.
In any mode (except when a setting screen is on the display), press (D) to illuminate the d splay



- Frequent display illumination can run down the battery quickly and require charging. The following guidelines give an idea of the charging time required to recover from a single illumination operation.
- Approximately 5 minutes exposure to bright sunlight coming in through a window Approximately 50 minutes exposure to indoor fluorescent lighting Be sure to read "Power Supply" for important information you need to know when exposing the watch to bright light.

If the display of the watch is blank ...

If the display of the watch is blank, it means that the watch's Power Saving function has turned off the display to conserve power.
See "Power Saving Function" for more information.

About This Manual



- Depending on the model of your watch, display text appears either as dark figures on a light background, or light figures on a dark background. All sample displays in this manual are shown using dark figures on a light background.
- In this manual are shown using dark figures on a light background.
 Button operations are indicated using the letters shown in the illustration.
 Each section of this manual provides you with the information you need in order to perform operations in each mode. Further details and technical information are be found in the "Defensero" content. can be found in the "Reference" section.






95858

LON

Stopwatch Mo

888888

STW



Radio-controlled Timekeeping



This watch receives a time calibration signal and updates its time setting accordingly. The time calibration signal includes both Standard Time and Daylight Saving Time

(summer time) data. • This watch is designed to pick up the time calibration signal transmitted from Rugby, England and the signal from Mainflingen, Germany.

Current Time Setting

This watch adjusts its time setting automatically in accordance with a time calibration signal. You can also perform a manual procedure to set the time and date. when necessary

1. In the Timekeeping Mode, hold down (A) until the city

Hour : Minutes : Seconds

- The first thing you should do after purchasing this watch is to set your Home City, which is the city where you will use the watch normally. For more information, see "To set your Home City".
- "To set your Home City". When using the watch in an area that is outside of the range of the transmitters in Rugby and Mainflingen, you need to adjust the time manually as required. See "Timekeeping" for information about manual settings.

To set your Home City

- 10,58/50 B 1111V 0 City code
- In the interkeeping wode, include own Lg, and the bit of years of the indicates the setting screen.
 Use ©(east) and (i) (west) to select the city code you want to use as your Home City.
 The following are the city codes for major cities in the Western Europe time zones.
 L I S: Lisbon
 L N: London
 E(TM) Barcelona BCN: Barcelona MAD: Madrid PAR·Paris MTL Milano ROM: Rome BER: Berlin STO: Stockholm
 - ATH: Athens
- 3. Press (A) to exit the setting screen.


Important!

- Normally, your watch should show the correct time as soon as you select your Home City code. If it does not, it should adjust automatically after the next auto receive operation (in the middle of the night). You also can perform manual receive or you can set the time manually
- If you are in an area that does not use Daylight Saving Time (summer time), turn off the DST setting.

Time Calibration Signal Reception

There are two different methods you can use to receive the time calibration signal: auto receive and manual receive

- Auto Receive Auto Receive With auto receive, the watch receives the time calibration signal automatically up to six times a day. When any auto receive is successful, the remaining auto receive operations are not performed. For more information, see "About Auto Receive".
- Manual Receive Manual receive Manual receive lets you start a time calibration receive operation with the press of a button. For more information, see "To perform manual receive".
- Important! When getting ready to receive the time calibration signal, position the watch as shown in the nearby illustration, with its 12 o'clock side facing towards a window. Make sure there are no metal objects nearby.



The watch should not be on its side or facing the wrong way.
 Proper signal reception can be difficult or even impossible under the conditions listed below.



- Signal reception normally is better at night than during the day. Time calibration signal reception takes from two to five minutes, but in some cases it can take as long as 12 minutes. Take care that you do not perform any button operations or move the watch during this time

CASIO

This watch is designed to receive the time calibration signal transmitted from Rugby, England and the signal from Mainflingen, Germany.

Reception Ranges



- At distances further than about 500 kilometers from a transmitter, signal reception
- At distances further that about 500 kilometers from a transmitter, signal reception may not be possible during certain times of year or times of day. Radio interference may also cause problems with reception.
 Even when the watch is within the reception range of the transmitter, signal reception is impossible if the signal is blocked by mountains or other geological formations between the watch and signal source.
 Signal reception is affected by weather, atmospheric conditions, and seasonal theorem.
- changes See the information under "Signal Receive Troubleshooting" if you experience problems with time calibration signal reception.

About Auto Receive With auto receive, the watch receives the time calibration signal automatically up to six times a day. When any auto receive is successful, the remaining auto receive operations are not performed. The start times of the auto receive operations depend on the current Home City and DST settings.

Home City		Auto Receive Start Times					
		1	2	3 4		5	6
LIS LON	Standard Time Daylight Saving Time	1:00 am 2:00 am	2:00 am 3:00 am	3:00 am 4:00 am	4:00 am 5:00 am	5:00 am Midnight	Midnight 1:00 am next day
BCN MAD PAR MIL ROM BER STO	Standard Time Daylight Saving Time	2:00 am 3:00 am	3:00 am 4:00 am	4:00 am 5:00 am	5:00 am Midnight	Midnight 1:00 am next day	1:00 am next day 2:00 am next day
ATH	Standard Time Daylight Saving Time	3:00 am 4:00 am	4:00 am 5:00 am	5:00 am Midnight	Midnight 1:00 am next day	1:00 am next day 2:00 am next day	2:00 am next day 3:00 am next day

- Auto receive works only while the watch is in the Timekeeping Mode or World Time Mode. Auto receive is not performed if an auto receive is is reached while an alarm is sounding, while a countdown timer operation is in progress, or while a setting screen (a screen with a flashing setting) is on the display.
 Auto receive of the calibration signal is designed to be performed early in the morning, while you sleep (provided that the Timekeeping Mode time is set correctly). Before going to bed for the night, remove the watch from your wrist, and put it in a location where it can receive the signal easily.
 When auto receive is turned on, the watch receives the calibration signal for two to five minutes everyday when the Timekeeping Mode time reaches each of the calibration times. Doing so can interfere with correct calibration.
 Remember that recepition of the calibration signal depends on the time keep in the Timekeeping Mode time display shows any one of the calibration times, regardless of whether or not the Timekeeping Mode time actually is the correct time.

About the Receiving Indicator

The receiving indicator shows the strength of the calibration signal being received. For best reception, be sure to keep the watch in a location where signal strength is strongest.



Even in an area where signal strength is strong, it takes about 10 seconds for signal reception to stabilize enough for the receiving indicator to indicate signal strength.
Use the receiving indicator as a guide for checking signal strength and for finding the best location for the watch during signal receive operations.

To perform manual receive

1. Place the watch on a stable surface so its top (12



Re

indicato

- Practice the watch of a stable surface so its top 12 o'clock side) is facing towards a window.
 In the Timekeeping Mode, hold down () for about two seconds until **RC** appears on the display.
 Time calibration signal reception takes from two to five
- minutes, but in some cases it can take as long as 12
- minutes. Take care that you do not perform any button operations or move the watch during this time. After signal reception is complete, the display of the watch changes to the Last Signal screen.

Note


- Note
 To interrupt a receive operation and return to the Timekeeping Mode, press ©.
 If the receive operation is unsuccessful, the message ERR appears on the display for about one or two minutes. After that, the watch returns to the Timekeeping Mode.
 You can also change from the Last Signal or ERR screen to the normal timekeeping screen by pressing ©.

To turn auto receive on and off



- In the Intervention work, press (C) to tabla the Last Signal screeen.
 Hold down (A) until the current auto receive setting (ON or OFF) starts to flash. This is the setting screen.
 Note that the setting screen will not appear if the currently selected Home City is one that does not support time calibration reception.
 Press (C) to torole auto receive on (ON) and off (OEF)
- Press © to toggle auto receive on (ON) and off (OFF).
 Press A to exit the setting screen.
 - For information about city codes that support signal receive, see "To set your Home City"

To display the Last Signal screen In the Timekeeping Mode, press C to display the Last Signal screen (indicated by GET). The Last Signal screen shows the date and time of the last successful time calibration signal reception



Signal Receive Troubleshooting

Check the following points whenever you experience problems with calibration signal reception.

Problem Probable Cause		What you should do
Cannot perform manual receive.	The watch is not in the Timekeeping Mode. Your current Home City is not one of the following city codes: LIS, LON, BCN, MAD, PAR, MIL, ROM, BER, STO or ATH.	 Enter the Timekeeping Mode and try again. Select LIS, LON, BCN, MAD, PAR, MIL, ROM, BER, STO, or ATH as your Home City.
Time setting is incorrect following signal reception.	 If the time is one hour off, the DST setting may be incorrect. The Home City code setting is not correct for the area where you are using the watch. 	 Change the DST setting to Auto DST. Select the correct Home City code.

For further information, see "Important!" under "Time Calibration Signal Reception" and "Radio-controlled Timekeeping Precautions".

World Time

Current time in selected city

- The World Time Mode shows you the current time in 48 cities (29 time zones) around the world. If the current time shown for a city is wrong, check your
- Home City time settings and make the necessary changes.
- All of the operations in this section are performed in the World Time Mode, which you enter by pressing B
- City code

45858

NYC.

0

B

6

To view the time in another city While in the World Time Mode, press C to scroll eastward through the city codes (time zones)

- To toggle a city code time between Standard Time and Daylight Saving Time

 1. In the World Time Mode, use © to display the city code (time zone) whose Standard Time/Daylight Saving Time setting you want to change.

 2. Hold down @ to toggle Daylight Saving Time (DST indicator displayed) and Standard Time (DST indicator or stiglayed) and Standard Tim

 - Indicator displayed) and standard time (UST indicator not displayed).
 The DST indicator will appear whenever you display a city code for which Daylight Saving Time is turned on.
 Note that the DST/Standard Time setting affects only the currently displayed city code. Other city codes are not diffected. affected

DST indica Alarms



6 Alam numbo To set an alarm time



The Alarm Mode gives you a choice of four one-time alarms and one snooze alarm. Also use the Alarm Mode to turn the Hourly Time Signal

- Also use the Alarm (SIG) on and off.
- ⇒ 1 G) on and on. There are five alarms numbered AL1 through AL4, and SNZ. You can configure SNZ as a snooze alarm only. Alarms AL1 through AL4 can be used as one-tion.
- All of the operations in this section are performed in the Alarm Mode, which you enter by pressing (B).

1. In the Alarm Mode, use (C) to scroll through the alarm screens until the one whose time you want to set is displayed.



For full information on city codes, see "City Code Table".

A 95858 B LON C 6

- 2. After you select an alarm, hold down (A) until the hour setting of the alarm time starts to flash, which indicates the setting screen.
- This operation turns on the alarm automatically

- Inis operation turns on the alarm automatically.
 Ise (B to move the flashing between the hour and minute settings.
 While a setting is flashing, use (C) (+) and (D) (-) to change it.
 Press (A) to exit the setting screen.
 When setting the alarm time using the 12-hour format, take care to set the time correctly as a.m. (no indicator) or p.m. (P indicator).

Alarm Operation The alarm tone sounds at the preset time for 10 seconds, regardless of the mode the watch is in. In the case of the snooze alarm, the alarm operation is performed a total of seven times, every five minutes, or until you turn the alarm off.

Pressing any button stops the alarm tone operation.
Performing any one of the following operations during a 5-minute interval between snooze alarms cancels the current snooze alarm operation.
Displaying the Timekeeping Mode setting screen Displaying the snooze alarm setting screen

To test the alarm In the Alarm Mode, hold down (C) to sound the alarm

To turn an alarm on and off

Alarm on indicator

LM SNZ+

- In the Alarm Mode, use © to select an alarm.
- 3:30 B SNZ C 0 Snooze alarm indicato
- 1 In the Alarm Mode, use ⓒ to select an alarm.
 2. Press ⓐ to toggle the alarm on and off.
 5. Turning on a one-time alarm (AL 1, AL Z, AL 3, (AL 4) displays the alarm on indicator on its Alarm Mode screen. Turning on the snooze alarm (SNZ) displays the alarm on indicator and snooze alarm indicator on its Alarm Mode screen.
 In all modes, the alarm on indicator is shown for any alarm that is turned on. When the snooze alarm is on, the snooze alarm indicator is alayed in all modes.
- the snooze alarm indicator is displayed in all modes The alarm on indicator flashes while the alarm is The snooze alarm indicator flashes during the 5-minute
- intervals between alarms

To turn the Hourly Time Signal on and off 1. In the Alarm Mode, use © to select the Hourly Time Hourly time signal

A

B

C

A


- In the Alarm Mode, use (C) to select the Houry Time Signal (SITE).
 Press (A) to toggle it on (Hourly Time Signal on indicator displayed) and off (Hourly Time Signal on indicator not displayed).
 The Hourly Time Signal on indicator is displayed in all modes when the Hourly Time Signal is turned on.

Countdown Timer

sig

:00

SIG



You can set the countdown timer within a range of one to 60 minutes. An alarm sounds when the countdown ches zero. rea

 All of the operations in this section are performed in the Countdown Timer Mode, which you enter by pressing (B).


b set the countdown start time While the countdown start time is on the display in the Countdown Timer Mode, hold down $\widehat{\otimes}$ until the current countdown start time starts to flash, which indicates the setting screen.

- If the countdown start time is not displayed, use the procedure under "To use the countdown time" to display it. 2. While a setting is flashing, use \bigcirc (+) and \bigcirc (-) to change it. 3. Press (A) to exit the setting screen.

To use the countdown timer

- Press © while in the Countdown Timer Mode to start the countdown timer.
- Press (© while in the Countdown Timer Mode to start the countdown timer. When the end of the countdown is reached, the alarm sounds for 10 seconds or until you stop it by pressing any button. The countdown time is reset automatically to its starting value after the alarm stops. Press (© while a countdown operation is in progress to pause it. Press (© again to resume the countdown operation completely, first pause it (by pressing (©)), and then press (a). This returns the countdown time to its starting value.

Stopwatch



- The stopwatch lets you measure elapsed time, split times, The stopward new your measure endpoint miles on the stopward innew, spin times and two finishes.
 The display range of the stopwatch is 59 minutes, 59.99 seconds.
- The stopwatch continues to run, restarting from zero

- The stopwatch continues to run, restarting from Zero after it reaches its limit, until you stop it.
 Exiting the Stopwatch Mode while a split time is frozen on the display clears the split time and returns to elapsed time measurement.
 The stopwatch measurement operation continues even if you exit the Stopwatch Mode.
 All of the operations in this section are performed in the Stopwatch Mode, which you eater the prosession (0)
- Stopwatch Mode, which you enter by pressing B

To measure times with the stopwatch

Flapsed Time

©	→©	→©	→©	→A
Start	Stop	Re-start	Stop	Clear
Split Time				
©	→@	→@	→©	→A
Start	Split (SPL displayed)	Split release	Stop	Clear
Two Finishes				
©	→A	→©——	→A	→A
Start	Split First runner finishes. Display time of first runner.	Stop Second runner finishes.	Split release Display time of second runner.	Clear

Illumination



The watch has an EL (electro-luminescent) panel that causes the entire display to glow for easy reading in the dark.

See "Illumination Precautions" for other important information

To turn on illumination

- In any mode (except when a setting screen is on the display), press () to illuminate the display. You can specify 1.5 seconds or 2.5 seconds as the illumination duration. See "To set the time and date" for more information

Power Supply

This watch is equipped with a solar cell and a special rechargeable battery (secondary battery) that is charged by the electrical power produced by the solar cell. The illustration shown below shows how you should position the watch for charging.


Example: Orient the watch so its face

- Example: Orient the watch so its face is pointing at a light source. The illustration shows how to position a watch with a resin band. Note that charging efficiency drops when any part of the solar cell is
- when any part of the solar cell is blocked by clothing, etc. You should try to keep the watch outside of your sleeve as much as possible. Charging is reduced significantly if the face is covered even sorticilly. partially

Solar cell

- Important!
 Storing the watch for long periods in an area where there is no light or wearing it in such a way that it is blocked from exposure to light can cause rechargeable battery power to run down. Make sure that the watch is exposed normally to bright light whenever possible.
- This watch uses a special rechargeable battery to store power produced by the solar This watch uses a special rechargeable battery to store power produced by the solar cell, so regular battery replacement is not required. However, after very long use, the rechargeable battery may lose its ability to achieve a full charge. If you experience problems getting the special rechargeable battery to charge fully, contact your dealer or CASIO distributor about having it replaced.
 Never try to remove or replace the watch's special battery yourself. Use of the wrong type of battery can damage the watch.
 The current time and all other settings return to their initial factory defaults whenever battery power drops to Level 4 and when you have the battery replaced.
 Turn on the watch's Power Saving function and keep it in an area normally exposed to bright light when storing it for long periods. This helps to keep the rechargeable battery from going dead.

Battery Power Indicator and Recover Indicator The battery power indicator shows you the current power level of the rechargeable battery.



- The LOW indicator flashes on the display in the Timekeeping Mode when battery is at Leve
- at Level 2. The LOW indicator at Level 2 and the flashing charge indicator (CHG) at Level 3 tell you that battery power is very low, and that exposure to bright light for charging is required as soon as possible. At Level 4, all functions are disabled and settings return to their initial factory defaults. Functions are enabled once again after the rechargeable battery is charged, but you need to set the time and date, after the battery reaches Level 3 (indicated by the flashing charge indicator) from Level 4. You will not be able to confinue any of the other settings until the battery reaches Level 1 after defaults. configure any of the other settings until the battery reaches Level 1 after dropping to Level 4
- Level 4. If you use the light or alarms a number of times during a short period, the recover indicator (RECOV) appears and the following operations become disabled until battery power recovers. *Illumination*
 - Beeper tone

Time calibration signal reception After some time, battery power will recover and the recover indicator will disappear, indicating that the above functions are enabled again.

CASIO

Charging Precautions

Charging Precautions Certain charging conditions can cause the watch to become very hot. Avoid leaving the watch in the areas described below whenever charging its rechargeable battery. Also note that allowing the watch to become very hot can cause its liquid crystal display to black out. The appearance of the LCD should become normal again when the watch returns to a lower temperature.

Warning!

Warning! Leaving the watch in bright light to charge its rechargeable battery can cause it to become quite hot. Take care when handling the watch to avoid burn injury. The watch can become particularly hot when exposed to the following conditions for long periods. On the dashboard of a car parked in direct sunlight Too close to an incandescent lamp Under direct sunlight

Under direct sunlight

Charging Guide

After a full charge, timekeeping remains enabled for up to about 8 months. • The following table shows the amount of time the watch needs to be exposed to light each day in order to generate enough power for normal daily operations

Exposure Level (Brightness)	Approximate Exposure Time
Outdoor Sunlight (50,000 lux)	5 minutes
Sunlight Through a Window (10,000 lux)	24 minutes
Daylight Through a Window on a Cloudy Day (5,000 lux)	48 minutes
Indoor Eluorescent Lighting (500 lux)	8 hours

Since these are the specs, we can include all the technical details.
Display on 18 hours per day, sleep state 6 hours per day
1 illumination operation (1.5 seconds) per day
10 seconds of alarm operation per day
10 minutes of signal reception per day
Stable operation is promoted by frequent exposure to light.

Recovery Times The table below shows the amount exposure that is required to take the battery from one level to the next.

Exposure Level	Approximate Exposure Time				
(Brightness)	Level 4	Level 3	Level 2	Level 1	
Outdoor Sunlight (50,000 lux)	2 hours 47		47 hours		
Sunlight Through a Window (10,000 lux)	6 hours 1		179 hours		
Daylight Through a Window on a Cloudy Day (5,000 lux)	10 hours			289 hours	
Indoor Fluorescent Lighting (500 lux)	104 hours				

The above exposure time values are all for reference only. Actual required exposure times depend on lighting conditions.


Timekeeping

- Use the Timekeeping Mode to set and view the current time and date. Vou can also use the Timekeeping Mode setting screen to specify the illumination duration and 12/24-hour format, to toggle power saving on and off, and to show or hide the date/day of the week on the main timekeeping screen. Under factory default settings, the main timekeeping screen shows the current time only (no date or day of the week). You can change the configuration of the watch so the main timekeeping screen also displays the date or day of the week. For details about how to do this, see "Displaying the Date or Day of the Week".

Viewing the Calendar Screen and Last Signal Screen

You can press (a) to display the current date and day of the week when they are not displayed in the main timekeeping screen. Pressing (C) displays the Last Signal Screen

If you leave the calendar screen displayed for two or three minutes without performing any operation, the watch will return to the main timekeeping screen automatically.



Last Signal Screen

Setting the Time and Date

Setting the Time and Date Make sure you select your Home City code before you change the current time and date settings. World Time Mode times are all displayed in accordance with the Timekeeping Mode settings. Because of this, World Time Mode times will not be correct if you do not select the proper Home City code before setting the time and date in the Timekeeping Mode.

To set the time and date



In the Timekeeping Mode, hold down (a) until the city code starts to flash, which indicates the setting screen.
 Press (b) to change the flashing contents in the sequence shown below to select other settings.



3. When the setting you want to change is flashing, use and/or to change it as described below.

Screen:	To do this:	Do this:
BER	Change the city code	Use © (east) and D (west).
DST AT	Cycle between auto DST (FT), Standard Time (OFF), and Daylight Saving Time (ON)	Press ©.
12H	Toggle between 12-hour (1 ≥H) and 24- hour (≥4H) timekeeping	Press ©.
50	Reset the seconds to	Press ©.
*	Toggle the illumination duration setting between 1.5 seconds (*) and 2.5 seconds (*)	Press D.
Change the hour, minutes, or year		Use © (+) and © (-).
20 05 6-30	Change the month or day	
00 PS	Toggle Power Saving on ([]]) and off ([]FF)	Press ©.
Show (current date displayed) or hide (indicated by) the date/day of the week on the main timekeeping screen		Press ©.

- See "City Code Table" for a complete list of available city codes.
 Auto DST (AT) can be selected only while L IS, LCN, BCN, MAD, PAR, MIL, ROM, BER, STO, or ATH is selected as the Home City code. For more information, see "Daylight Saving Time (DST)" below.
 For information about settings other than the time and date, see the following. *Illumination Unitation: Illumination*
- Power Saving: Power Saving Function For details about showing or hiding the date/day of the week, see "Displaying the Date or Day of the Week". 4. Press (a) to exit the setting screen.

Daylight Saving Time (DST)

Daylight Saving Time (summer time) advances the time setting by one hour from Standard Time. Remember that not all countries or even local areas use Daylight

Standard Time. Hereinneer that not all countries or even local areas use Daylight Standard Time. The time calibration signals transmitted from Rugby and Mainflingen include both Standard Time and DST data. When the Auto DST setting is turned on, the watch switches between Standard Time and DST (summer time) automatically in accordance with the received time signal. The default DST setting is Auto DST (HT) whenever you select LIS, LON, ECN, MRD, FAR, MIL, ROM, EER, STO, or ATH as your Home City code. If you experience problems receiving the time calibration signal in your area, it probably is best to switch between Standard Time and Daylight Saving Time (summer time) manually.

- (summer time) manually.
- To change the Daylight Saving Time (summer time) setting
 1. In the Timekeeping Mode, hold down (A) until the city code starts to flash, which indicates the setting screen.
 2. Press (B) and the DST setting screen appears.
 3. Use (C) to cycle through the DST settings in the sequence shown below.

. 036 ()	Use (c) to cycle through the DOT settings in the sequence shown below.					
┌→	Auto DST (AT)	⊢	DST off (OFF)	⊢	DST on (ON)	h

4. When the setting you want is selected, press (A) to exit the setting screen.
The DST indicator appears to indicate that Daylight Saving Time is turned on.


Displaying the Date or Day of the Week

Displaying the Date of Day of the week Under factory default settings, the main timekeeping screen shows the current time only (no date or day of the week). You can change the configuration of the watch so the main timekeeping screen also displays the date or day of the week. You can select either the date or the day of the week for display along with the current time on the main timekeeping screen. • For information about how to specify the contents of the main timekeeping screen, see "To show and hide the date/day of the week on the main timekeeping screen, while display of the date/day of the week is turned on for the main timekeeping screen, you can press (a) to togothe between display of the date (month and day) and

- screen, you can press (A) to toggle between display of the date (month and day) and the day of the week.

CASIO

Toggling between the Date and Day of the Week on the main timekeeping Screen



To show and hide the date/day of the week on the main timekeeping screen

- To show and hide the date/day of the week on the main timekeeping screen 1. In the Timekeeping Mode, hold down (Å) until the city code starts to flash, which indicates the setting screen. 2. Press (Å) 10 times so the current date/day of the week setting is flashing. The current date will be flashing if the date/day of the week currently are shown, while — will be flashing if they are hidden. 3. Press (Å) to toggle the date/day of the week between show (current date displayed) and birde — displayed)
- and hide (--- displayed). 4. Press (A) to exit the setting screen.

Reference

This section contains more detailed and technical information about watch operation. It also contains important precautions and notes about the various features and functions of this watch.

Button Operation Tone



The button operation tone sounds any time you press one of the watch's buttons. You can turn the button operation tone on or off as desired

Even if you turn off the button operation tone, the alarm, Hourly Time Signal, and Countdown Timer Mode alarm all operate normally.

MUTE indicato

- To turn the button operation tone on and off In any mode (except when a setting screen is on the display), hold down (a) to toggle the button operation tone on (MUTE not displayed) and off (MUTE displayed). Since the B button is also the mode change button, holding it down to turn the
- button operation tone on or off also causes the watch's current mode to change The **MUTE** indicator is displayed in all modes when the button operation tone is turned off

Power Saving Function



When turned on, the Power Saving function enters a sleep state automatically whenever the watch is left in an area where it is dark for a certain period. The table below shows how watch functions are affected by the Power ving function

er saving indicato

Elapsed Time in Dark	Display	Operation
60 to 70 minutes	Blank, with Power Saving indicator (PS) flashing	All functions enabled, except for the display
6 or 7 days Blank, with Power Saving indicator (PS) not flashing		Beeper tone, illumination, and display are disabled.

Wearing the watch inside the sleeve of clothing can cause it to enter the sleep state. The watch will not enter the sleep state between 6:00 AM and 10:59 PM. If the watch is already in the sleep state when 6:00 AM arrives, however, it will remain in . The watch will not enter the sleep state betwee the sleep state

To recover from the sleep state Perform any one of the following operations. • Move the watch to a well-lit area.

A

C

B

· Press any button

.17

TIPS

To turn Power Saving on and off

- and on
 and o
- modes while Power Saving is turned on.

-______ On/Off statu

Auto Return Features

- If you leave the watch in the Alarm Mode for two or three minutes without performing any operation, it returns to the Timekeeping Mode automatically. If you leave the watch with a flashing setting on the display for two or three minutes without performing any operation, the watch exits the setting screen automatically.

Scrolling The \bigcirc and O buttons are used in various modes and setting screens to scroll through data. In most cases, holding down these buttons during a scroll operation scrolls through the data at high speed.

Initial Screens

When you enter the World Time or Alarm Mode, the data you were viewing when you last exited the mode appears first.

Radio-controlled Timekeeping Precautions

- Hadio-controlled Timekeeping Preclations
 Strong electrostatic charge can result in the wrong time being set.
 The time calibration signal is bounced off the ionosphere. Because of this, such factors as changes in the reflectivity of the ionosphere, as well as movement of the ionosphere to higher altitudes due to seasonal atmospheric changes or the time of day may change the reception range of the signal and make reception temporarily impossible.
- Even if the time calibration signal is received properly, certain conditions can cause
- Even if the time calibration signal is received properly, certain conditions can cause the time setting to be off by up to one second.
 The current time setting in accordance with the time calibration signal takes priority over any time settings you make.
 The watch is designed to update the date and day of the week automatically for the period January 1, 2000 to December 31, 2099. Setting of the date by a time calibration signal cannot be performed starting from January 1, 2100.
 This watch has receive signed, that differentials between leave near each open and performed starting from January 1, 2100.
- . This watch can receive signals that differentiate between leap years and non-leap
- This watch can receive signals that differentiate between leap years and non-leap years.
 Though this watch is designed to receive both time data (hour, minutes, seconds) and date data (year, month, day), certain signal conditions can limit reception to ti data only.
- oata only. Normally, the signal reception date shown by the Last Signal screen is the date data included in the received time calibration signal. When only time data is received, however, the Last Signal screen shows the date as kept in the Timekeeping Mode at
- If you are in an area where proper time calibration signal reception.
 If you are in an area where proper time calibration signal reception is impossible, the watch keeps time within ±20 seconds a month at normal temperature.
 If you have problems with proper time calibration signal reception or if the time setting is wrong after signal reception, check your current city code, DST (summer time), and auto receive settings. The following are the initial factory defaults for these orthinger settings.

Setting	Initial Factory Default
City code	BER (Berlin)
DST (summer time)	a⊤ (Auto switching)
Auto receive	ON (Auto receive)

Transmitters

This watch is designed to receive the time calibration signal transmitted from Rugby, England and the signal from Mainflingen, Germany.

first

In this case:	The watch does this:
The first signal auto search operation after factory default settings are in effect, or after the city code has been changed	 Checks the Mainflingen signal first. If the Mainflingen signal cannot be received, checks the Rugby signal.
Any case other than the above.	 Checks the last successfully received signal first. If the last successfully received signal cannot be received, checks the other signal.

Timekeeping

- Timekeeping
 Resetting the seconds to 00 while the current count is in the range of 30 to 59 causes the minutes to be increased by 1. In the range of 00 to 29, the seconds are reset to 00 without changing the minutes.
 The day of the week is displayed automatically in accordance with the date (year, month, and day) settings.
 The year can be set in the range of 2000 to 2099.
 The watrix built-in full automatic calendar makes allowances for different month lengths and leap years. Once you set the date, there should be no reason to change it except after you have the watch's battery replaced or when battery power drops to I avei 4. Level 4
- Level 4. The times for the Timekeeping Mode and all the city codes of the World Time Mode are calculated in accordance with each city's UTC differential. The UTC differential is a value that indicates the time difference between a reference point in Greenwich, England and the time zone where a city is located. The letters "UTC" is the abbreviation for "Universal Time Coordinated", which is the world-wide scientific standard of timekeening. It is based upon carefully maintained atomic (cesium) clocks that keep time accurately to within microseconds. Leap seconds are added or subtracted as necessary to keep UTC in sync with the Earth's

12-hour/24-hour Timekeeping Formats

The 12-hour/24-hour timekeeping format you select in the Timekeeping Mode is also applied in all other modes.

- With the 12-hour format, the PM indicator (P) appears on the display for times in the range of noon to 11:59 p.m. and no indicator appears for times in the range of midnight to 11:59 a.m. With the 24-hour format, times are displayed in the range of 0:00 to 23:59, without
- any indicator

Illumination Precautions

- The electro-luminescent panel that provides illumination loses power after very long use Illumination may be hard to see when viewed under direct sunlight
- The watch may emit an audible sound whenever the display is illuminated. This is due to vibration of the EL panel used for illumination, and does not indicate
- The formation of the EL participation in the mathematical, and see a mathematical in the second seco

City Code Table

City Code	City	UTC Differential	Other major cities in same time zone
PPG	Pago Pago	-11.0	
HNL	Honolulu	-10.0	Papeete
ANC	Anchorage	-09.0	Nome
YVR	Vancouver	-08.0	San Francisco, Las Vegas,
LAX	Los Angeles	-08.0	Seattle/Tacoma, Dawson City
YEA	Edmonton	-07.0	El Paso
DEN	Denver	-07.0	Li Faso
MEX	Mexico City		
YWG	Winnipeg	-06.0	Houston, Dallas/Fort Worth, New Orleans
CHI	Chicago		
MIA	Miami		Montreal, Detroit, Boston,
YTO	Toronto	-05.0	Panama City, Havana, Lima, Bogota
NYC	New York		Fallallia Olty, Havalla, Ellia, Bogola
CCS	Caracas	-04.0	La Paz, Santiago, Port Of Spain
YHZ	Halifax	••	La raz, Saniiayo, ron Or Spall
YYT	St. Johns	-03.5	
RIO	Rio De Janeiro	-03.0	Sao Paulo, Buenos Aires, Brasilia, Montevideo
RAI	Praia	-01.0	
LIS	Lisbon		Dublin Occubioco Deles Abbilina
LON	London	+00.0	Dublin, Casablanca, Dakar, Abidjan
BCN	Barcelona		
MAD	Madrid	1	
PAR	Paris	1	
MIL	Milan	+01.0	Amsterdam, Algiers, Hamburg, Frankfurt, Vienna
ROM	Rome	1	
BER	Berlin		
STO	Stockholm		
ATH	Athens		Helsinki, Istanbul, Beirut, Damascus,
CAI	Cairo	+02.0	Cape Town
JRS	Jerusalem		Cape lowin
MOW	Moscow	+03.0	Kuwait, Riyadh, Aden, Addis Ababa, Nairobi
JED	Jeddah		
THR	Tehran	+03.5	Shiraz
DXB	Dubai	+04.0	Abu Dhabi, Muscat
KBL	Kabul	+04.5	
KHI	Karachi	+05.0	Male
DEL	Delhi	+05.5	Mumbai, Kolkata
DAC	Dhaka	+06.0	Colombo
RGN	Yangon	+06.5	
BKK	Bangkok	+07.0	Jakarta, Phnom Penh, Hanoi, Vientiane
HKG	Hong Kong	+08.0	Singapore, Kuala Lumpur, Beijing, Taipei, Manila, Perth, Ulaanbaatar
SEL	Seoul	+09.0	Pyongyang
TYO	Tokyo		
ADL	Adelaide	+09.5	Darwin
GUM	Guam	+10.0	Melbourne, Rabaul
SYD	Sydney		
NOU	Noumea	+11.0	Port Vila
WLG	Wellington	+12.0	Christchurch, Nadi, Nauru Island

Based on data as of June 2005.

CASIO.